

# SP3-TCM+

## Transport Control Module

IR control system for up to 5 VCRs, DVD players, monitors, satellite tuners, and more



SP3-TCM+ 1GANG-BL  
Single-Gang TCM+ (black)

- ▼ Control as many as five devices
- ▼ Perfect fit with VCR/DVD combo units
- ▼ Learns IR codes from almost any remote



- ▼ Only programmed buttons illuminate
- ▼ Cloning allows quick programming of many units



SP3-TCM+ 1GANG-AG  
Single-Gang TCM+  
(anodized gray)

### FEATURES

The Transport Control Module provides a simple, standardized control interface for as many as five IR-controllable devices, such as VCRs, DVD players, monitors, satellite tuners, and more.

Only the buttons used for the device being controlled are illuminated. When you switch between the devices the TCM+ controls, different buttons illuminate.

### EASY TO INSTALL

The TCM+ is a perfect fit with the SmartPanel™ control system, or operates on its own. Switch between programmed devices using relay closure.

### EASY TO CONFIGURE

With IR learning, the TCM+ can learn the remote control of your display devices in minutes. No programming is necessary, so leave the laptop at home.



Programmed to control standard VCR



Programmed to control DVD player



**Simple.**  
**Intuitive.**  
**Control.**

SP Controls, Inc.  
930 Linden Avenue  
South San Francisco  
California 94080  
phone: (877) 367-8444  
fax: (650) 392-7881  
email: help@spcontrols.com

### TECHNICAL SPECIFICATIONS

Power Supply:	8-13V DC, 220mA
Dimensions:	2.6" (h) x 2.4" (w) x 1.4" (d) 65mm (h) x 62mm (w) x 35mm (d)
Weight:	2.5 oz
Connectors:	Female DB9 RS-232 (configuration port) (1) 2-pole captive screw (power) (1) 5-pole captive screw (relay switch control) (1) 5-pole captive screw (IR emitter output)
Temperature/Humidity:	Storage -40° to +158°F (-40° to +70°C)/10% to 90% non-condensing Operating +32° to +122°F (0° to +50°C)/10% to 90% non-condensing